

PWC 5.0 2021



Standard equipment:

- 3.700.0030 Gun M22 - 3/8" with rotating coupling



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0056 Nozzle type 075 (mod. 2021 LP)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling.
- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- Integrated elastic joint, for best pump coupling.
- Low voltage and delayed Total Stop.
- Suction and delivery S/S valves.
- Integrated detergent suction with external suction probe.
- Pressure regulator.
- Glycerine pressure gauge.
- Hose-reel (**optional**).
- Steel frame.
- Steel covers.

Optional:

- cod. 6.608.0068 High-pressure hose-reel (hose not included)



Integrated elastic joint, for best pump coupling

PWC 5.0 2021	
code	8.654.0076
operat. pressure	200 bar-2900 psi
delivery rate	1260 l/h-5.55 GPM
abs. power/voltage	9400W - 400V-50Hz 3ph
pump type/RPM	MPW5/1450 RPM
max. water inlet temperature	40 °C
dimension/weight	50x90x83cm / 58 Kg - 128 lbs