

NEW

KRON ZERO R Vantage



- Capable to work for the maintenance and deep cleaning of large areas (up to 3.700 m²) with a very important reduction of cost of cleaning
- More than 50 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Compact size (810 mm)
- Stability even when fully loaded, front independent wheeldrive with tight steering radius
- Recovery tank control window for cleaning and easy ordinary maintenance
- Easy access to electrical components
- Automatic device that stops brushes and detergent water outflow when the machine is stationary
- Self-levelling brushes

Standard equipment:



Kron ZERO R 75 Vantage

- 2 x 5.511.1168
PPL brush Ø 360 mm - 14"



Kron ZERO R 85 Vantage

- 2 x 5.511.1688
PPL brush Ø 430 mm - 17"



Kron ZERO R 75 Vantage

- 4.508.0646
Front squeegee blade L.925 mm
Shore 40 Th. 3 mm
- 4.508.0605
Rear squeegee blade L.1015 mm
Shore 30 Th. 4 mm

Kron ZERO R 85 Vantage

- 4.508.1196
Front squeegee blade L.1027 mm
Shore 40 Th. 3 mm
- 4.508.1195
Rear squeegee blade L.1150 mm
Shore 33 Th. 4 mm



Watch the video on youtube:
www.youtube.com/ctmcleaning

	KRON ZERO R 75 Vantage	KRON ZERO R 85 Vantage
code	8.576.3001	8.576.3002
power supply	24V	24V
scrubbing / squeegee width	750 / 900 mm	850 / 900 mm
max working capacity	3750 m ² /h	4100 m ² /h
detergent tank capacity	110 l / 29.05 gal	110 l / 29.05 gal
recovery tank capacity	130-155 l / 34.35-40.95 gal	130-155 l / 34.35-40.95 gal
traction type / power	front motorwheel / 600 W	front motorwheel / 600 W
RPM / pressure on the brushes	150/50 kg / 110.23 lbs	150/50 kg / 110.23 lbs
brush motor power	2 x 400 W	2 x 400 W
max gradient empty/full tank	13% / 10%	13% / 10%
depression / vacuum motor	1300 mmH ₂ O/400W	1300 mmH ₂ O/400W
dimensions / weight	146x81x138 cm / 220 kg	146x81x138 cm / 220 kg



The detergent water tank serves as battery compartment, allowing the housing of great capacity batteries granting continuous working time. Large capacity shock and acid proof polyethylene tank (110 l) improves productivity avoiding frequent refilling and idle time.

Simple and intuitive controls reduce operator's training time. Easy mechanical brush plate and squeegee lifting system, for low maintenance costs. The enbloc brush plate apply a very high pressure (50 kg) to the floor, strongly and deeply removing any kind of dirt.



New control panel with digital controls and display. Digital display: with hour meter, battery charge level indicator, empty water tank level indicator and forward/reverse traction indicator. Speed control adjustment, horn, suction motor switch with delayed switch-off, brush plate lifting/lowering selector switch,

brush motor switch. The ergonomic and comfortable shape of the machine allows the operator to work effortless for a long time, improving productivity.



Optional accessories:



- 4 x 0.107.0004 Tubular battery Pb-acid 6V 180Ah C5 + 2 x 5.511.0561 connection cable batteries



- 4 x 0.107.0072 GEL Battery 6 MFP 180 6V 180Ah C5



- 0.108.0002 Battery Charger 24V 25A 220-240/50-60




- 5.511.1641 On-board Battery charger kit - 24V - 20A



- 4.508.0901 Polyurethane front blade L.925 TH.3 Sh.40
- 4.508.0900 Polyurethane rear blade L.1015 TH.4 Sh.40
- 4.508.1251 Polyurethane front blade L.1027 TH.3
- 4.508.1252 Polyurethane rear blade L.1150 TH.4



- 5.511.1246 Tynex brush Ø 360 mm-14"
- 5.511.1169 PPL 0,03 brush Ø 360 mm-14"
- 5.511.1203 PES brush Ø 360 mm - 14"



- 5.511.1713 Tynex brush Ø 430 mm-17"
- 5.511.1711 PPL 0,03 brush Ø 430 mm-17"
- 5.511.1712 PES brush Ø 430 mm - 17"



- 5.511.1592 EWU pad driver Ø 380 mm-15"
- 5.511.1095 EWU pad driver Ø 406 mm-17"



- 6.508.0143 - Ø 380 mm - 15"- beige (5 pcs.)
- 6.508.0144 - Ø 380 mm - 15"- green (5 pcs.)
- 6.508.0141 - Ø 380 mm - 15"- black (5 pcs.)
- 6.508.0032 - Ø 406 mm - 17"- beige (5 pcs.)
- 6.508.0039 - Ø 406 mm - 17"- green (5 pcs.)
- 6.508.0046 - Ø 406 mm - 17"- black (5 pcs.)